

Typical Features

- ◆ Fixed input voltage, Isolated & unregulated, Output power 2W
- ◆ Efficiency up to 86% (Typ.)
- ◆ Mini size DIP package
- ◆ Isolation Voltage 3000VDC
- ◆ Operating Temperature from -40°C to +105°C
- ◆ Plastic Case, flame class UL94 V-0



Test Condition: Unless otherwise specified, all parameter values had been tested at nominal input voltage, pure resistive rated load, and at room temperature 25°C.

Application Field

This series of products can be widely used in the fields of instrument, communication, pure digital circuit, general low frequency analog circuit, relay drive circuit, data exchange circuit, etc.

Typical Product List

Certificate	Part No.	Input Voltage Range (VDC)		Output Voltage/Current (Vo/Io)		Input Current (mA) Typ. @Nominal Voltage		Max. Capacitive Load	Ripple & Noise (20MHz) Max/Typ.	Efficiency (%) @Full load/Nom. voltage	
		Nom.	Range	Vo (VDC)	Io(mA) Max/Min	Full Load	No Load	uF	mVp-p	Min	Typ.
-	NN2-05S3V3F3N	5	4.5 - 5.5	3.3	400/40	513	8	2400	150	74	78
-	NN2-05S05F3N			5	400/40	476	8	1200	150	77	80
-	NN2-05S12F3N			12	167/17	455	18	560	150	77	80
-	NN2-05S15F3N			15	133/13	455	20	560	150	80	83
-	NN2-05S24F3N			24	83/8	450	15	220	150	79	82
-	NN2-12S05F3N	12	10.8 - 13.2	5	400	195	10	2400	150	81	84
-	NN2-12S12F3N			12	167	186	10	1200	150	83	86
-	NN2-12S15F3N			15	133	192	10	560	150	80	83
-	NN2-24S05F3N	24	21.6 - 26.4	5	400	98	8	2400	150	79	82
-	NN2-24S12F3N			12	167	95	8	1200	150	83	86
-	NN2-24S15F3N			15	133	96	8	560	150	80	83
-	NN2-05D05F3N	5	4.5 - 5.5	±5	±200	476	8	1200	150	77	80
-	NN2-05D12F3N			±12	±83	455	18	220	150	77	80
-	NN2-05D15F3N			±15	±67	455	20	220	150	77	80
-	NN2-12D05F3N	12	10.8 - 13.2	±5	±200	195	10	1200	150	81	84
-	NN2-12D12F3N			±12	±83	186	10	220	150	83	86
-	NN2-12D15F3N			±15	±67	192	10	220	150	80	83

-	NN2-24D05F3N	24	21.6	±5	±200	98	8	1200	150	79	82
-	NN2-24D12F3N		-	±12	±83	95	8	220	150	83	86
-	NN2-24D15F3N		26.4	±15	±67	96	8	220	150	80	83

Note: The ripple & noise are tested by the twisted pair method.

Input Specifications

Item	Operating Condition	Min.	Typ.	Max.	Unit
Input Inrush Voltage (1Sec max.)	3.3Vdc input	-0.7	--	7	Vdc
	5Vdc input	-0.7	--	9	
	9Vdc input	-0.7	--	12	
	12Vdc input	-0.7	--	18	
	15Vdc input	-0.7	--	21	
	24Vdc input	-0.7	--	30	
Input Filter	Capacitor Filter				
Hot Plug	Unavailable				

Output Specifications

Item	Operating Condition	Min.	Typ.	Max.	Unit
Output Power		0.2	--	2	W
Output Voltage Accuracy	Refer to the Output Voltage Deviation Graph (Figure 1)				
Load Regulation	10% -100% load	3.3V output	--	15	%
		Others	--	10	
Line Voltage Regulation	Input voltage change ±1%	3.3V output	--	1.5	--
		Others	--	1.2	
Temp. Drift Coefficient	100% Load	--	--	±0.03	%/°C
Short Circuit Protection	Continuous, self-recovery				

General Specifications




Item	Operating Condition	Min.	Typ.	Max.	Unit
Switching Frequency	Nominal input voltage, full load	--	260	--	KHz
Operating Temperature	Refer to the Temperature Derating Graph (Figure 2)	-40	--	+105	°C
Storage Temperature		-55	--	+125	
Case temperature rise	Ta=25°C	--	30°	--	
Pin soldering temperature	1.5mm from the case, 10S	--	--	300	
Relative Humidity	No condensing	5	--	95	%RH
Isolation Voltage	I/P-O/P, test 1 minute, leakage current <1mA	3000	--	--	VDC

Insulation Resistance	I/P-O/P @ 500VDC	1000	--	--	M Ω
Isolation Capacitor	I/P-O/P, 100KHz/0.1V	--	20	--	pF
Vibration	10-150Hz, 5G, 30 Min. along X, Y and Z				
MTBF	MIL-HDBK-217F@25°C	3500	--	--	K hours
Case Material	Plastic in Black, flame class UL94-V0				
Unit Weight	2.5g (Typ.)				
Cooling Method	Natural air				
Packing	Tube size (525x18x10mm)		25PCS/Tube		
	Carton size (542x110x155mm)		2000PCS/Carton (Total 80 Tubes)		
Unit Dimensions	L x W x H	20.00× 10.00 × 6.80 mm		0.787 × 0.394 × 0.270 inch	

EMC Performance

EMI	CE	CISPR32/EN55032 CLASS B (with the Recommended EMC circuit)
	RE	CISPR32/EN55032 CLASS B (with the Recommended EMC circuit)
EMS	ESD	IEC/EN61000-4-2 Contact ±6kV perf.Criteria B

Mechanical Dimensions



PCB layout vertical view

Grid 2.54x2.54[0.10x0.10]

Unit: mm[inch]

Pin diameter tolerance: ±0.10[±0.004]

General tolerance: ±0.50[±0.020]

Pin Function Description


Pin No.	1	7	8	9	10	14
Single output	GND	No Connection	+Vout	No Pin	-Vout	+Vin
Dual outputs	GND	No Connection	+Vout	COM	-Vout	+Vin

Note: Please take the pin definition on the product label as the right one if there is any difference between the data sheet and the one printed on the product.

Ripple & Noise Test Instruction (Twisted Pair Method, 20MHz bandwidth)

1) The Ripple & noise test needs 12# twisted pair cables, an oscilloscope which bandwidth should be set to 20MHz, 0.1uF polypropylene capacitor and 10uF high-frequency low-resistance electrolytic capacitor are connected in parallel with the probes (100M bandwidth). The oscilloscope should be set at the Sample Mode.

2) The test diagram is shown on the right. The converter output connects to the electronic load by the jig with cables which size should be defined according to the output current value. The twisted pair (length $30\text{cm} \pm 2\text{cm}$) should be connected in parallel with the load, the location is as close as possible to the output pins or terminals. The test can be start after input power on.



Product Characteristics Graphs




Figure 1




Figure 2


Recommended Circuits Diagrams for Application

1. Requirement for Output load

The maximum capacitive load was tested at the rated full load. The converter may not start or be damaged if the output capacitors exceed this value.

2. Typical application circuit


To ensure effectively decrease the input and output ripple and noise, a capacitor filter can be connected at the input and output, the application circuit is shown in the figure below. The suitable filter capacitors should be chosen as the recommended capacitive load values in Table 1. The converter could not start if the capacitance is too big.



Recommended Capacitive Load Value Table (Table 1)

V_{in} (Vdc)	C_{in}	Single V_{out} (Vdc)	C_{out} (μF)	Dual V_{out} (Vdc)	C_{out} (μF)
5	10 μF /16V	3.3	10 μF /16V	± 3.3	4.7 μF /16V
12	2.2 μF /25V	5	10 μF /16V	± 5	4.7 μF /16V
15	2.2 μF /25V	9	2.2 μF /25V	± 9	2.2 μF /25V
24	1 μF /50V	12	2.2 μF /25V	± 12	1 μF /25V
--	--	15	1 μF /25V	± 15	1 μF /16V
--	--	24	1 μF /50V	± 24	0.47 μF /50V

3. Recommended EMC Circuit Diagrams





Input voltage		5VDC	12/15/24VDC
EMI	C1/C2	4.7 μF /16V	4.7 μF /50V
	CY	270pF/3KV	270pF/3KV
	C3	Refer to C_{out} in Table 1	
	LDM	6.8 μH	6.8 μH

Input voltage		5VDC	12/15/24VDC
EMI	C1/C2	4.7 μF /16V	4.7 μF /50V
	CY	270pF/3KV	270pF/3KV
	C3/C4	Refer to C_{out} in Table 1	
	LDM	6.8 μH	6.8 μH

4. Output voltage regulation and overvoltage protection

The simple solution to achieve the output regulated voltage, over voltage and over current protections is to connect a linear regulator with overheat protection at input or output, and a capacitor filter connected in parallel as below circuit. Filter capacitive value recommended see table 1, Linear regulator should be chosen according to the actual voltage & current for operating. Or Aipu NW series products are recommended instead.





Dual outputs

Application Notice

1. This series of converters should not be used in parallel, and they do not support hot-plugging.
2. The product performance in this datasheet cannot be guaranteed if it works at a lower load than the minimum load condition.
3. All values or indicators in this datasheet had been tested based on Aipupower test specifications.

Guangzhou Aipu Electron Technology Co., Ltd

Address: Building 4, HEDY Park, No.63, Punan Road, Huangpu Dist, Guangzhou, China.

Tel: 86-20-84206763 Fax: 86-20-84206762 HOTLINE: 400-889-8821

E-mail: sales@aipu-elec.com Website: <https://www.aipupower.com>